

## ZH350ST

Compact short throw Full HD laser projector









- Bright Full HD 1080p DuraCore laser projector -3500 lumens and IP6X certified
- Compact and short throw lens for easy installation
   360-degree and portrait projection
- Reduced power consumption for a long life span -DuraCore laser technology delivers 30,000 hours maintenance free laser light source
- External power supply More reliability, portability and energy efficiency



The ZH350ST is one of Optoma's most compact and hassle-free Full HD 1080p DuraCore laser projectors to date. Designed for maintenance-free continuous operation, this 3500-lumen projector delivers powerful image performance with flexible installation features and extensive connectivity options in a sleek, compact form factor, up to 34% smaller than previous Optoma models.<sup>1</sup>

An added benefit, the ZH350ST features an external power supply offering more reliability, portability and energy efficiency.

## **Specifications**

EAN: 5055387666795, Colour: White

UPC: 796435 44 657 4, Colour: White

Display/image

Display technology DLPTM

**Resolution** 1080p Full HD (1920x1080)

 Brightness
 3.500 lumens

 Contrast ratio
 300.000:1

 Contrast ratio - dynamic
 2.000.000:1

 Native aspect ratio
 16:9

 Aspect ratio - compatible
 4:3,16:9,16:10

Keystone correction -

+/-30°

 Keystone correction - vertical
 +/-30°

 Displayable colours (millions)
 1073.4

 Horizontal scan rate
 15 ~ 140Khz

 Vertical scan rate
 24 ~ 120Hz

 Uniformity
 75%

**Screen size** 0.76m ~ 7.62m (30" ~ 300") diagonal

Lamp info

horizontal

Light source type Laser
LASER life 30.000 hours

Optical

Throw ratio 0.496:1

Projection distance (m) 0.3m - 3.3m

Zoom type Fixed

Focal length (mm) 7.51

Native offset 116%

Connectivity

Connections Inputs 2 x HDMI 2.0

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

Control 1 x RS232

General

Noise level (min) 27dB Noise level (max) 34dB

PC compatibility

FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac

2D compatibility

NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H//M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p,

720p/50/60Hz), 1080i/50/60Hz), 1080p/50/60Hz)

**3D compatibility** Yes (DLP 3D; PC frame sequential 120Hz 3D, Blu-ray DVD 3D)

720p50 / 60

**3D** Full 3D

Security Security bar, Kensington Lock, Password protected interface

IP rating IP6X

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnamese

24/7 operation Yes 360° operation Yes

**Operating conditions** 0°C ~ 40°C, Max. Humidity 80%, Max. Altitude 2,500m

 Remote control
 Card style

 Speaker count
 1

 Watts per speaker
 15W

In the box AC power cord Remote control

Remote control 1x CR2025 battery Basic user manual 8.60ms

 Input lag
 8.60ms

 Optional wireless models
 UHDCast Pro

Power

**Power supply** 100V ~ 240V, 50-60Hz

 Power consumption (standby)
 <0.5W</td>

 Power consumption (min)
 98W

 Power consumption (max)
 139W

Weight and dimensions

 Dimensions (W x D x H) mm
 274 x 216 x 114

 Gross weight
 4.2 kg

 Net weight
 3 kg





