

## DH351

High resolution presentations









- Lights on viewing 3600 ANSI lumens
- Easy connectivity HDMI, USB power
- Portable and lightweight
- Built-in audio

Project bright Full HD 1080p images with the DH351. Perfect for classroom and meeting room presentations, this projector is designed to be used at any time of day.



Additionally, it boasts ease of use with its single HDMI connection and built-in speaker. You can even use the USB power to connect and power HDMI dongles such as the Google Chromecast.

## **Specifications**

EAN: 5055387663701, Colour: Black

Display/image Display technology

DIPTM

Resolution 1080p Full HD (1920x1080)

Brightness 3.600 lumens Contrast ratio 22.000:1 Native aspect ratio 16:9 Aspect ratio - compatible 4:3 Keystone correction - vertical +/-40° Uniformity

80%

Screen size 0.71m ~ 7.65m (28" ~ 301") diagonal

Lamp info Light source type 240 Lamp watts

4000 (Bright), 15000 (Dynamic), 10000 (Eco) Lamp life hours (up to) Optical

Throw ratio 1.47:1 ~ 1.62:1 Projection distance (m) 1m - 9.8m

Zoom 1.1 Zoom type Manual

15.59mm~17.14mm/0.614"~0.675" Focal length (mm)

Native offset 116%

Connectivity Connections

Inputs 1 x HDMI 1.4a 3D support

Outputs 1 x Audio 3.5mm, 1 x USB-A power 1.5A

General

3D

Noise level (typical) 26dB 28dB Noise level (max)

PC compatibility FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 2D compatibility NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz

SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)

Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 3D compatibility

Full 3D

Security Security bar, Kensington Lock, Password protected interface

OSD / display languages 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,

Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional),

Turkish, Vietnames

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 85%

Remote control Backlit home remote

Speaker count 5W Watts per speaker

In the box AC power cord

2x AAA batteries Basic user manual HDCast Pro, WHD200

Optional wireless models Power

Power supply 100 ~ 240V, 50 ~ 60Hz

0.5W Power consumption (standby) 205W Power consumption (min) 295W Power consumption (max)

Weight and dimensions

Dimensions (W x D x H) mm 316 x 244 x 108 Gross weight 3.81 kg 2.8 kg Net weight





