

ZU920TST

Ultra bright professional installation laser projector



- 9800 lumen DuraCore laser projector Ultra bright for immersive installations
- Full motorized lens shift Ideal for a simple set up
- Large zoom range Motorized zoom expands placement opportunities
- Long life Delivers 30,000 hours of virtually maintenance-free operation



At 9800 lumens with 4K and HDR compatibility, the ZU920TST features
a dust-resistant IP5X certified optical engine for 24/7 operation
capabilities, offering true maintenance-free projection for up to 30,000 hours of powerful performance in Eco mode. Other features include
a motorized zoom and focus, full motorized lens shift, and built-in dual 10W speakers.

High brightness, color precision and quiet operation, along with a short throw lens make this projector the ideal solution for a variety of end-user scenarios and professional environments, such as short throw digital signage, edge-blending and projection mapping, simulation and immersive installations.

Specifications

UPC: 796435 44 590 4, EAN: 5055387666047, Colour: black

 Display/image
 DLP

 Display technology
 DLP

 Resolution
 WUXGA (1920x1200)

 Brightness
 9.800 lumens

 ANSI brightness
 8.200

 Contrast ratio
 3.000.000:1

ANSI prigntness 8.200

Contrast ratio 3.000.000:1

Contrast ratio - full on/off 1.100:1

Native aspect ratio 16:10

Aspect ratio - compatible 4:3,16:9,16:10

Keystone correction - 30°

horizontal

Keystone correction - vertical 30°

Uniformity 95%

Screen size 1.27m ~ 7.62m (50" ~ 300") diagonal

 Lamp info
 DuraCore Laser

 Light source type
 DuraCore Laser

 LASER life
 30.000 hours

 Optical

Lens shift Vertical: +/-55%, Horizontal: +/-25%

Native offset 50%

Lens shift Yes - {{downloads_link}}

Connectivity Connections

onnections Inputs 1 x HDBaseT, 1 x HDMI 2.0, 1 x HDMI 2.0, 1 x VGA,

1 x 3D sync, 1 x Audio 3.5mm

Outputs 1 x HDMI 2.0, 1 x 3D sync, 1 x USB-A power 1.5A,

1 x Audio 3.5mm

Control 1 x 12V trigger, 1 x Wired remote, 1 x RJ45, 1 x

RS232

LAN - wireless networking No

 General
 36dB

 Noise level (typical)
 38dB

 Noise level (max)
 38dB

Security Security bar, Kensington Lock

OSD / display languages 9 languages: English, French, German, Italian, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional)

24/7 operationYes360° operationYes

Remote control Backlit ProAV remote

 Speaker count
 2

 Watts per speaker
 10W

 In the box
 Power Cable QSG Lens Cap

Networking LAN - wireless networking No

LAN Yes
Power

 Power supply
 AC 90 – 264V 50/60 Hz

 Power consumption (min)
 260W

Power consumption (max) 505W

Weight and dimensions

 Dimensions (W x D x H) mm
 486 x 417.4 x 176

 Gross weight
 17.5 kg

 Net weight
 14 kg





