

UHD35

4K UHD gaming and home entertainment projector









- 4K UHD resolution HDR and HLG compatible
- Lights on viewing 3600 lumens
- Supports 1080p 240Hz for smooth gaming and an ultra-low input lag of 4.2ms
- Full 3D compatible

Immerse yourself in a world of Ultra HD gaming, live sports, TV shows and movies. The UHD35 delivers impressive 4K cinema-quality images, lightning-fast input lag as low as 4.2ms and a high refresh rate of 240Hz for silky smooth gaming.

TV and movie fans can also enjoy excellent colour depth, crystal clear detail, and sparkling contrast for a stunningly immersive experience.

Packed with the latest technology and features, this stylish projector boasts High Dynamic Range (HDR) and HLG compatibility, Full 3D and two HDMI 2.0 ports. Perfect for enjoying life-like big-screen entertainment in any living space.



Specifications

Display/image DIPTM Display technology Resolution UHD (3840x2160) Brightness 3.600 lumens 1.000.000:1 Contrast ratio 16:9 Native aspect ratio Aspect ratio - compatible 4:3 Keystone correction -+/-40° horizontal Keystone correction - vertical +/-40° Horizontal scan rate 31 ~ 135Khz Vertical scan rate 24 ~ 120Hz Uniformity 80% 0.84m ~ 7.62m (33" ~ 300") diagonal Screen size Lamp info

Light source type Lamp watts 240 Lamp life hours (up to)

4000 (Bright), 15000 (Dynamic), 10000 (Eco)

Optical Throw ratio 1.5:1 ~ 1.66:1 Projection distance (m) 1.21m - 9.9m Zoom 1.1 Manual Zoom type

Focal length (mm) 15.84 mm~17.42mm/0.624"~0.686"

Lens shift Vertical +0% Native offset 105%

Connectivity

Connections Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio

Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power

Control 1 x RS232, 1 x 12V trigger

General Noise level (typical) 26dB 28dB Noise level (max)

PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA,

SVGA, VGA, Mac

480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) 2D compatibility

3D compatibility Frame-pack: 1080p24, 720p50 / 60

3D Full 3D

Security Security bar, Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max

humidity 85%

Remote control Backlit home remote

Watts per speaker 10W In the box AC power cord Remote control

2x AAA batteries Basic user manual

Input lag 4.20ms

Power

100 ~ 240V, 50 ~ 60Hz Power supply

Power consumption (standby) 0.5W 220W Power consumption (min) Power consumption (max) 305W

Weight and dimensions

315 x 270 x 118 Dimensions (W x D x H) mm Gross weight 4.68 kg 3.98 kg Net weight





