

# HZ40ST

Compact high brightness short throw home entertainment laser projector



- **Lights on viewing - 4200 lumens**
- **Full HD 1080p laser projector - 4K UHD and HDR compatible**
- **Short throw lens - 100" image from just over a metre away**
- **Easy connectivity – 2x HDMI, USB Power and 10W speaker**



Feel the action and experience every moment on the big screen with the HZ40ST. Perfect for immersive live sports, TV shows, movies and gaming.

Convenient and easy to set-up, this compact high brightness short throw laser projector is ideal for well-lit environments so sports fans can enjoy live action with family or friends with the lights on.

# Specifications

EAN: 5055387664630, Colour: White

|                                       |  |
|---------------------------------------|--|
| <b>Display/image</b>                  |  |
| Display technology                    | DLP™   |
| Resolution                            | 1080p Full HD (1920x1080)  |
| Brightness                            | 4,200 lumens   |
| Contrast ratio                        | 2,500,000:1  |
| Native aspect ratio                   | 16:9   |
| Aspect ratio - compatible             | 4:3  |
| Keystone correction - horizontal      | +/-15°   |
| Keystone correction - vertical        | +/-15°   |
| Has vertical auto keystone correction | Yes  |
| Displayable colours (millions)        | 1073.4   |
| Horizontal scan rate                  | 15,375 ~ 91.146 KHz  |
| Vertical scan rate                    | 50 ~ 85 Hz (120Hz for 3D)Hz  |
| Uniformity                            | 80%  |
| Screen size                           | 0.93m ~ 7.66m (36.43" ~ 301.4") diagonal   |
| <b>Lamp info</b>                      |  |
| Light source type                     | Laser  |
| LASER life                            | 30,000 hours   |
| <b>Optical</b>                        |  |
| Throw ratio                           | 0.5:1  |
| Projection distance (m)               | 0.4m - 3.31m   |
| Zoom type                             | Fixed  |
| Focal length (mm)                     | 7.51   |
| Native offset                         | 115%   |
| <b>Connectivity</b>                   |  |
| Connections                           | <b>Inputs</b> 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB), 2 x Audio 3.5mm, 1 x Microphone<br><b>Outputs</b> 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1.5A<br><b>Control</b> 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x micro USB service, 1 x 3D sync     |
| <b>General</b>                        |  |
| Noise level (typical)                 | 30dB   |
| Noise level (max)                     | 32dB   |
| PC compatibility                      | UHD, FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac  |
| 2D compatibility                      | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)  |
| 3D compatibility                      | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D   |
| 3D                                    | Full 3D  |
| Security                              | Security bar, Kensington Lock, Password protected interface  |
| IP rating                             | IP6X   |
| OSD / display languages               | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| 24/7 operation                        | Yes  |
| 360° operation                        | Yes  |
| Operating conditions                  | 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m   |
| Remote control                        | Backlit ProAV remote   |
| Speaker count                         | 2  |
| Watts per speaker                     | 10W  |
| In the box                            | AC power cord<br>Remote control<br>2x AAA batteries<br>Basic user manual   |
| Input lag                             | 8.20ms   |
| Optional wireless models              | HDCast Pro, QuickCast Bundle, QuickCast starter kit  |
| <b>Networking</b>                     |  |
| LAN - control                         | Yes  |
| <b>Power</b>                          |  |
| Power supply                          | 100 ~ 240V, 50 ~ 60Hz  |
| Power consumption (standby)           | <0.5W  |
| Power consumption (min)               | 206W   |
| Power consumption (max)               | 269W   |
| <b>Weight and dimensions</b>          |  |
| Dimensions (W x D x H) mm             | 337 x 265 x 122.5  |
| Gross weight                          | 6.22 kg  |
| Net weight                            | 4.5 kg   |

