

UHD38

Bright 4K UHD gaming and home entertainment projector









- 4K UHD resolution HDR and HLG compatible
- Lights on viewing 4000 lumens for use any time of day
- Lightning fast gaming projector Delivers 1080p 240Hz with an ultra-low input lag of 4.2ms
- Full 3D compatible Experience life-like bigscreen entertainment



Immerse yourself in a world of Ultra HD gaming, live sports and TV shows. The UHD38 delivers impressive bright 4K UHD quality images, lightning-fast input lag as low as 4.2ms and a high refresh rate of 240Hz - perfect for a competitive gaming advantage.

Packed with the latest technology and features, this stylish projector boasts High Dynamic Range (HDR) and HLG compatibility, Full 3D and two HDMI 2.0 ports. Perfect for enjoying life-like big-screen entertainment in any living space.

Specifications

EAN: 5055387665378, Colour: White

Display/image DLP™ Display technology Resolution UHD (3840x2160) 4.000 lumens Brightness Contrast ratio 1.000.000:1 Native aspect ratio 16.9 Aspect ratio - compatible 4:3 +/-40° Keystone correction horizontal Keystone correction - vertical +/-40° Horizontal scan rate 31 ~ 135Khz 24 ~ 120Hz Vertical scan rate 80% Uniformity

0.84m ~ 7.62m (33" ~ 300") diagonal Screen size

Lamp info Light source type Lamp 240 Lamp watts

4000 (Bright), 15000 (Dynamic), 10000 (Eco) Lamp life hours (up to)

Optical 1.5:1 ~ 1.66:1 Throw ratio Projection distance (m) 1.21m - 9.9m Zoom 1.1 Zoom type Manual

Focal length (mm) 15.84 mm~17.42mm/0.624"~0.686"

Lens shift Vertical +0% Native offset 105%

Connectivity Connections

Remote control

Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio

Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power

Control 1 x RS232, 1 x 12V trigger

General 26dB Noise level (typical) Noise level (max) 28dB

PC compatibility UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA,

SVGA, VGA, Mac

480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2160p(50/60Hz) 2D compatibility

Frame-pack: 1080p24, 720p50 / 60 3D compatibility

3D Full 3D

Security bar, Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish

Operating conditions 5°C~40°C/41°F~104°F, max altitude 3000M/9843ft, max humidity 85%

Backlit home remote

Speaker count Watts per speaker 10W In the box AC power cord

Remote control 2x AAA batteries Basic user manual

Input lag 4.20ms Power

100 ~ 240V, 50 ~ 60Hz Power supply

0.5W Power consumption (standby) Power consumption (min) 220W Power consumption (max) 305W

Weight and dimensions

Dimensions (W x D x H) mm 315 x 270 x 118 4.68 kg Gross weight Net weight 3.98 kg





