

X402

Bright, powerful and business ready



- **Bright XGA projector – 4200 ANSI lumens**
- **Crestron RoomView® – RJ45 control and monitoring**
- **Easy connectivity – HDMI, VGA and built-in 10W speaker**
- **Lightweight and portable - Carry bag included**



Project bright vibrant widescreen presentations any time of day. Designed for meeting rooms and classrooms, the X402 boasts a long lamp life and energy-saving features which provide a low overall cost of ownership.

This projector has a built-in speaker, networking capabilities, Full 3D technology and HDMI connectivity. It is also lightweight so can be installed or taken on the move in the handy carry bag for off-site meetings.

Specifications

EAN: 5055387600157, Colour: White



| | |
|----------------------------------|---|
| Display/image | |
| Display technology | DLP™ |
| Resolution | XGA (1024x768) |
| Brightness | 4,200 lumens |
| Contrast ratio | 20,000:1 |
| Native aspect ratio | 16:9 |
| Aspect ratio - compatible | 4:3 |
| Keystone correction - horizontal | +/-0° |
| Keystone correction - vertical | +/-40° |
| Horizontal scan rate | 15.3 ~ 91.1Khz |
| Vertical scan rate | 24 ~ 85(120 for 3D)Hz |
| Uniformity | 80% |
| Screen size | 0.78m ~ 7.8m (30.8" ~ 307") diagonal |
| Lamp info | |
| Light source type | Lamp |
| Lamp watts | 260 |
| Lamp life hours (up to) | 3000 (Bright), 5500 (Dynamic), 5000 (Eco), 7000 (Eco+) |
| Optical | |
| Throw ratio | 1.6:1 ~ 1.92:1 |
| Projection distance (m) | 1.2m - 12m |
| Zoom | 1.2 |
| Zoom type | Manual |
| Focal length (mm) | 18.2 ~ 21.9 |
| Native offset | 115% |
| Connectivity | |
| Connections | Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB/wireless), 1 x VGA (YPbPr/RGB), 1 x Composite video, 2 x Audio 3.5mm Outputs 1 x VGA (YPbPr/RGB), 1 x Audio 3.5mm Control 1 x RS232, 1 x RJ45, 1 x 3D sync, 1 x mini USB mouse/service |
| General | |
| Noise level (typical) | 31dB |
| Noise level (max) | 33dB |
| PC compatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4.43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) |
| 3D compatibility | Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Full 3D |
| 3D | |
| Security | Security bar, Kensington Lock, Password protected interface |
| OSD / display languages | 20 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Italian, Norwegian, Polish, Portuguese, Romanian, Russian, Spanish, Swedish, Turkish |
| Operating conditions | 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m |
| Remote control | Data remote with laser and mouse function |
| Speaker count | 1 |
| Watts per speaker | 10W |
| In the box | Carry bag AC power cord Remote control 2x AAA batteries Basic user manual |
| Optional wireless models | QuickCast Bundle, QuickCast starter kit, WHD200 |
| Networking | |
| LAN - control | Yes |
| Power | |
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Power consumption (min) | 257W |
| Power consumption (max) | 306W |
| Weight and dimensions | |
| Dimensions (W x D x H) mm | 315 x 224 x 102 |
| Gross weight | 4.1 kg |
| Net weight | 2.57 kg |

